

RC 110



Extremely robust and strong



Formidable cutting strength



Replacement of knives and screen in record time



Easy hydraulic change of screen



Smooth and silent operation



High capacity



Voracious like a crocodife

| Special screen lighting device | Screen replacement only takes a few minutes |
|--------------------------------|--|
| All knife fastening screws are | Very quick knife replacement by pneumatic or electric screw driver |
| protected | |
| Friction clutch | Protection against overload and damage of rotor |
| V-belt drive | More silent running |
| Externally placed rotor | Protection of bearings from dirt |
| bearing | |
| Heavy flywheel | Formidable cutting power |
| No oversize | Fits in a standard box container |

| Technical Specification | MODEL RC 110 |
|---|--------------|
| Required floor area | |
| Height | |
| Rotor length | |
| Cutting circle diameter | 450 mm |
| No. of rotor knives | |
| No. of fixed knives | _ |
| No. of rotor knife rows | 3 pcs |
| No. of fixed knife rows | 1 pcs |
| Rotor speed | 115 rpm |
| Motor, rated input | 110 kW |
| Weight (approximate) | |
| Screen hole size (choice of different s | izes) |

Screen hole size (choice of different sizes)

Capacity for copper cable (depending on type):

•with screen Ø 20 mm.....approx. 2.5 t/h

•with screen Ø 40 mm.....approx. 4.0 t/h

Transmission: Motor - V-belt drive - intermediate shaft - V-belt drive - flywheel with friction coupling.

With reservation for technical alterations.

Special device for replacement of the screen.



Quick replacement of screen




VAT No.: **BG040002183**

Bulgarian Chamber of Commerce and Industry Registration Number: 1017244600 / 24.02.1992

Massive rotor with tremendous cutting strength.








Rough Chopper RC 110 is best suited for the medium throughput cable recycling plant.

The design is extremely robust with an extraordinary cutting strength. It is like a crocodile - with sharp, triangular teeth – that quickly devours all kinds of cable.

The rough chopper is preferably fed by means of a grab. Cables are cut into finger-size pieces, ideally suited for automatic feeding into the cable recycling plant.

Due to the helical arrangement of the rotor knives the machine is very smooth and silent in operation, with no need for noise dampening or special foundation.

The plant is specially designed for easy and quick maintenance. The individual knives are easily accessible and quick to replace. Both fixed and rotor knives can be sharpened some eight times on any standard surface grinding machine.





VAT No.: BG040002183

Bulgarian Chamber of Commerce and Industry Registration Number: 1017244600 / 24.02.1992