

2SC1946A

NPN EPITAXIAL PLANAR TYPE

DESCRIPTION


2SC1946A is a silicon NPN epitaxial planar type transistor designed for RF power amplifiers on VHF band mobile radio applications.

OUTLINE DRAWING

Dimensions in mm

C1.5MAX 4.0 ± 0.5 C1.5MAX

- Emitter ballasted construction and gold metallization for high reliability and good performances.
- Low thermal resistance ceramic package with flange.
- Ability of withstanding more than 20:1 load VSWR when operated at $V_{CC} = 15.2V$, $P_O = 30W$, $f = 175MHz$.
- Equivalent input/output impedance at rated operating conditions: $Z_{in} = 0.65 + j1.4\Omega$
 $Z_{out} = 1.9 + j0.75\Omega$



Symbol	Parameter	Conditions	Ratings	Unit
V_{CBO}	Collector to base voltage		35	V
V_{EBO}	Emitter to base voltage		4	V
V_{CEO}	Collector to emitter voltage	$R_{BE} = \infty$	17	V
I_C	Collector current		7	A
P_C	Collector dissipation	$T_a = 25^\circ C$	3	W
		$T_C = 25^\circ C$	50	W
T_j	Junction temperature		175	$^\circ C$
T_{stg}	Storage temperature		-55 to 175	$^\circ C$
R_{th-a}	Thermal resistance	Junction to ambient	50	$^\circ C/W$
R_{th-c}		Junction to case	3	$^\circ C/W$

Note: Above parameters are guaranteed independently.

ELECTRICAL CHARACTERISTICS ($T_C = 25^\circ C$ unless otherwise specified)

Symbol	Parameter	Test conditions	Limits			Unit
			Min	Typ	Max	
$V_{(BR)EBO}$	Emitter to base breakdown voltage	$I_E = 10mA, I_C = 0$	4			V
$V_{(BR)CBO}$	Collector to base breakdown voltage	$I_C = 10mA, I_E = 0$	35			V
$V_{(BR)CEO}$	Collector to emitter breakdown voltage	$I_C = 0.1A, R_{BE} = \infty$	17			V
I_{CBO}	Collector cutoff current	$V_{CB} = 25V, I_E = 0$			2	mA
I_{EBO}	Emitter cutoff current	$V_{EB} = 3V, I_C = 0$			1	mA
h_{FE}	DC forward current gain *	$V_{CE} = 10V, I_C = 0.2A$	10	50	180	—
P_O	Output power	$V_{CC} = 13.5V, P_{in} = 3W, f = 175MHz$	30	35		W
η_C	Collector efficiency		60	70		%


Note: * Pulse test, $P_w = 150\mu s$, duty=5%.

Above parameters, ratings, limits and conditions are subject to change.

MITSUBISHI RF POWER TRANSISTOR 2SC1946A

NPN EPITAXIAL PLANAR TYPE


TEST CIRCUIT




L: Length 10mm
 RFC: 0.4mm enameled wire 12T with Ferrite Bead
 CB1: 220pF, 2200pF in parallel
 CB2: 220pF, 2200pF, 10μF in parallel

Notes: All coils are made from 1.5mmφ silver plated copper wire
 Coil dimensions in milli-meter
 D: Inner diameter of coil
 T: Turn number of coil


TYPICAL PERFORMANCE DATA




COLLECTOR TO EMITTER VOLTAGE




COLLECTOR TO EMITTER BREAKDOWN VOLTAGE VS. BASE TO EMITTER RESISTANCE




DC CURRENT GAIN VS. COLLECTOR CURRENT



COLLECTOR OUTPUT CAPACITANCE VS. COLLECTOR TO BASE VOLTAGE



OUTPUT POWER, COLLECTOR EFFICIENCY VS. INPUT POWER



OUTPUT POWER VS. COLLECTOR SUPPLY VOLTAGE

