

# Starling Nationals Measurement Form

**Boat No.** \_\_\_\_\_ **Skipper's Name** \_\_\_\_\_

"A" certificate registered in surname of entrant

Hull shall be clean, dry and stripped of everything except permanently attached fittings.

Mast	OK	SIGNATURE
Aluminium Fosters section, no lightening holes		
Continuous within 10mm of straight		
Length overall, 4480mm, including washers, (excuding base pin)		
Thickness of mast base spacer washer _____ mm		
Forestay and sidestay position, 2875 +/- 75mm from mast base		
Sealed mast or 10 mm diameter drain hole		

## Boom

Aluminium Fosters section, no lightening holes		
Continuous – within 10mm of straight		
Sail track top continuous min 2000mm		

## Centreboard

Dimensions under the cheeks max 1067mm x 280mm		
Lanyard securing centreboard to hull		

## Rudder

From deck c/line to rudder tip max 840mm		
Width max 254mm		
Forward point of blade no more than 30mm aft of gudgeons c/line		
Gudgeons c/line max 38mm to tuck		
Rudder stock secured to boat		
Tiller secured to rudder stock		

## Sail

Hood or North Insignia. Sail number same as hull number.		
No Seam Alterations		

## Hull

"A" Certificate Sighted		
Towing attachment point practical & secure.		
Bow jig able to clear bow, handle and attachment screws.		
Aft face of mast 610mm +/- 6mm from C frame		
Mast step height max 20mm above deck		
No holes in "C" frame		
Hand bailer attached		
Centre case free of water excluders on hull opening.		
Insignia and number on sides 50mm min.		
Hawse centre line max 50mm from transom.		

**Weight**

Weight 41.0kg Min.		
Corrector weights attached only to aft cockpit bulkhead.		
Weight added _____ Kg		

**Lifejacket**

Skipper's weight within jacket flotation range.		
-------------------------------------------------	--	--

<b>FINAL OK:</b> Everthing signed off.	
-------------------------------------------	--